



DPH-130SE

As a highly user-friendly business IP phone, the D-Link DPH-130SE features a 2.4" 320*240-pixel color LCD display, providing a clear visual experience for users. It supports up to 4 SIP accounts and includes local 5-way conferencing. With its adjustable multi-angle stand, the DPH-130SE IP phone ensures flexibility in various working situations. Moreover, its easy-to-use interface, powerful features, and reasonable pricing deliver an excellent voice communication solutions

Key Features

- **Stronger Performance, More Possibilities**

Featuring a powerful chipset, the DPH-130 series demonstrates excellent performance, capable of extending services to meet various business demands

- **Superior HD Audio, Better Communication**

With its leading Smart Noise Filtering Technology, this device delivers excellent sound quality by eliminating extraneous noises, allowing for fluent conversations.

- **Classic Design, Practical Details**

The DPH-130 features a user-friendly operation interface, offering users a more comfortable and ideal operational experience.

- HD Voice
- 2.4" Color LCD display
- 320*240 Pixels
- Two 10/100M Ethernet Ports
- Support Opus codec
- 4 SIP accounts
- Local 5-way conferencing
- Stand with 2 adjustable angles
- Wall mountable
- PoE Power

Audio Features

- Voice: handset, speaker, headset
- Smart Noise Filtering
- Wideband codec: Opus, G.722
- Narrowband codec: G.711(A/μ), G.729, G.729A, iLBC
- DTMF: RFC 2833, SIP INFO, Inband
- Full-duplex hands-free speakerphone with AEC
- VAD, CNG, AEC, PLC, AJB, AGC

Phone Feature

- 4 SIP accounts
- Call hold, DND, Speed dial
- Call forward, call waiting, call transfer
- Redial, call return, auto answer
- Local 5-way conferencing
- Direct IP call, Time/Date Management

Directory

- Local phonebook up to 1000 entries
- Blacklist
- XML/LDAP remote phonebook
- Smart dialing
- Phonebook search/import/export
- Call history: dialed/received/missed

Package

- Package content:
- DPH-130SE IP phone
- Handset with handset cord
- Ethernet Cable (1.5m CAT5E UTP Cable)
- Stand
- Quick Start Guide
- QIG

Display & Indicator

- 2.4" 320*240 –pixel color graphical LCD display
- LED for call and message waiting indication
- illuminated LED for line status information
- Intuitive user interface with icons and soft keys
- Multilingual user interface
- Caller ID with name and number

Function Keys

- 4 line keys, 5 navigation keys
- 6 features keys: message, headset, redial, mute, hands-free speakerphone
- Volume control keys

Network Security

- SIP v1(RF2543), v2(RFC3261)
- NAT traversal: STUN
- Proxy and peer-to-peer SIP
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- SNTP
- UDP/TCP/DNS-SRV (RFC 3263)
- SRTP/ SIP TLS
- HTTPS certificate manager
- IPv6
- DHCP VLAN/LLDP

Management

- Configure via browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS
- TR-069, System log
- Reset to factory, reboot

IP-PBX Features

- BLF, Anonymous call
- Anonymous call rejection
- Call park, call pickup

Other Physical Features

- 2 * RJ-45 10/100Mbps
- 1 * RJ9 (4P4C) Handset
- 1 * RJ9 (4P4C) Headset
- Wall Mountable
- Power Adapter(Optional)
- 100-240VAC Input, DC 5V/1A Output
- Power Consumption:2~3W
- Dimension(W*D*H*T): 188mm*189mm*162mm*50mm
- Operating humidity: 10~95%
- Operating temperature: -10~50°C (+14~122°F)